

**ARDON®**

TECHNICAL DATA SHEET

M1000


Eye protection

Article NO: E4016


Lens: clear
Material- lens: polycarbonate
Material- frame: nylon



Safety glasses with the black nylon frame and black nylon temples with red strip combine protective properties with fashionable sports look. They have adjustable temples tilt, thanks to which the glasses fit every user perfectly. Wide clear polycarbonate lens protect against UV radiation, it is anti-fogging, anti-scratching and resistant to low-energy shocks (up to 45 m/s) at extreme temperatures (-5 °C - +55 °C) and provides maximum protection. Soft black grooved non-sliding nose bridge ensures excellent all-day wear. They provide extremely large field of view.



Adjustable temple length - YES



Adjustable temple angle - YES



Anti-fogging lens - YES



Anti-scratching lens - YES

Clear lens, UV, 2-1.2 1 FT 0

| | | |
|------------------------|-----|--------------------------------------------------------|
| Type of filter: | 2 | UV filter |
| Shade number: | 1.2 | clear |
| Optical class: | 1 | permanent use |
| Mechanical resistance: | FT | resistant to low-energy shocks at extreme temperatures |
| Type of the lens: | 0 | original lens |



This personal protective equipment is in conformity with these harmonized European Standards:

EN 166:2001: Personal eye protection. General requirements.

EN 170:2002: Personal eye-protection - Ultraviolet filters - Transmittance requirements and recommended use.

Certified by Notified body no. 2797 (BSI Group The Netherlands B.V., John M. Keynesplein 9, 1066 EP Amsterdam, The Netherlands),
Certificate no CE 749754, dated 26th August 2021.

| | |
|---------------------------|----------------------|
| Pieces in carton: | 250 |
| Pieces in box: | 10 |
| Polybag packing (pieces): | 1 |
| Carton weight: | 13 kg |
| Carton size: | 0,103 m ³ |

Store in dry and dark environment away from direct sunlight at temperatures of -5°C to +55°C, relative humidity 90% and out of sources of gasoline vapors and solvents.

It is recommended to clean after each use. Clean at room temperature with a clean cloth, lightly moistened with a concentrated solution of water and detergent. Do not use hot water, fuel, degreasing fluids, organic solvents or abrasive cleaners.
