



ARDON®
WORKWEAR
& OUTDOOR

ARDON® RASPER S1P

SAFETY SHOES



DRY AIR



**DEFUSE
CONTROL**



NONMETALLIC



REFLECTIVE



ARDON®
WORKWEAR
& OUTDOOR

ARDON® RASPER S1P

SAFETY SHOES

ARTICLE

G3164

MATERIAL

Upper
Lining
Sole

brushed cowhide VELOR / fabric
MESH laminated breathable fabric
PU/rubber, two-component spray coating, oil resistant, anti-static,
antislip, resistant up to 300 °C
composite 604
kevlar
ANATOMIC FOAM anatomically shaped EVA foam

Toe cap
Plate
Insole

SIZE

36-48

UNIT

pair

PACKAGE

Units in a carton
Units in a box

10 pairs
1 pair

DIMENSIONS

Carton H x W x D
(cm)
Carton (cbm)

36-39
31.5 x 41.5 x 61.5
0,0804

40-43
33.5 x 43.5 x 61.5
0,0896

44-48
37 x 43.5 x 64
0,103

Size EUR	35	36	37	38	39	40	41	42	43	44	45	46	47	48	49	50	51
Insole length mm	-	237	243	250	257	263	270	277	283	290	297	303	310	317	-	-	-
Foot length cm	-	23,2	23,8	24,5	25,2	25,8	26,5	27,2	27,8	28,5	29,2	29,8	30,5	31,2	-	-	-

DESCRIPTION

Safety low shoes with upper made of VELOR material and the fabric.

The wide PU / rubber sole has SRC anti-slip properties and is resistant to contact

heat up to 300 ° C. The ANATOMIC FOAM insole ensures increased comfort of the shoes. The

shoes are equipped with a composite toe and a flexible Kevlar insole against punctures.

NORMS















(EU) 2016/425

EN ISO 20345:2011

Personal protective equipment – Safety footwear

Category

S1P HRO SRC

Categories	EN ISO 20345	
E - energy absorption in the heel area	✓	
FO - resistance to oils and fuels	✓	
A - antistatic footwear	✓	
SRC - resistance to slipping on ceramic floor tiles with SLS and on steel floors with glycerin	✓	
WR - upper resistant to water		
Safety toe cap for toe protection	✓	
P - resistance to punctures (protective insole)	✓	
SRA - slip resistance ceramic floor tiles with SLS		
HRO - resistance to contact heatup to 300 °C	✓	
HI-insulation of the bottom of the shoe against heat		
CI-insulation of the bottom of the shoe against the cold		
Splatters of molten metal		
ESD – shoe protects against electrostatic discharge and can be used on EPA premises		
The shoes do not contain metal parts	✓	
-		
-		
-		



ARDON®
WORKWEAR
& **OUTDOOR**

CODE	EAN	CARTON WEIGHT (KG)	UNIT WEIGHT (KG)
G3164/36	8592390068989	12.25	1.225
G3164/37	8592390068996	12.75	1.275
G3164/38	8592390069009	13.35	1.335
G3164/39	8592390069016	13.55	1.355
G3164/40	8592390069023	13.85	1.385
G3164/41	8592390069030	14.45	1.445
G3164/42	8592390069047	14.80	1.480
G3164/43	8592390069054	15.15	1.515
G3164/44	8592390069061	15.95	1.595
G3164/45	8592390069078	16.30	1.630
G3164/46	8592390069085	16.75	1.675
G3164/47	8592390069092	17.20	1.720
G3164/48	8592390069108	17.50	1.750



ARDON®
WORKWEAR
& **OUTDOOR**





ARDON®

**WORKWEAR
& OUTDOOR**

