

**ARDON®**

TECHNICAL DATA SHEET

M6000


Eye protection

Article NO: E4050


Lens: clear
Material - lens: polycarbonate
Material - frame: EVA foam
Material - temples: nylon



Lightweight protective glasses for maximum protection. The inner edge of the lens is bounded by a soft EVA foam, which ensures a better fit, shock absorption and effective seal. The temples have a soft finish. Black ventilated nose bridge ensures a comfortable fit. Clear visor is anti-fogging, anti-scratching and resistant to low-energy shocks (up to 45 m / s) even at extreme temperatures (-5 ° C - + 55 ° C).



Adjustable temple length - NO



Adjustable temple angle - NO



Anti-fogging lens - YES



Anti-scratching lens - YES

Clear lens, 2-1.2 1 FT 0

Type of the filter:	2	UV filter
Shade number:	1.2	clear lens
Optical class:	1	permanent use
Mechanical resistance:	FT	resistant to low-energy shocks at extreme temperatures
Type of the lens:	0	original lens



This personal protective equipment is in conformity with these harmonized European Standards:

EN 166:2001: Personal eye protection. General requirements.

EN 170:2002: Personal eye-protection - Ultraviolet filters - Transmittance requirements and recommended use.

Certified by Notified body no. 2797 (BSI Group The Netherlands B.V., John M. Keynesplein 9, 1066 EP Amsterdam, The Netherlands), Certificate no CE 749754, dated 26th August 2021.

Pieces in carton:	250
Pieces in box:	10
Polybag packing (pieces):	1
Carton weight:	11 kg
Carton size:	0,105 m ³

Store in dry and dark environment away from direct sunlight at temperatures of -5°C to +55°C, relative humidity 90% and out of sources of gasoline vapors and solvents.

It is recommended to clean after each use. Clean at room temperature with a clean cloth, lightly moistened with a concentrated solution of water and detergent. Do not use hot water, fuel, degreasing fluids, organic solvents or abrasive cleaners.
