





FA 60 0006 10/20:

PVC +  **STEEL**

FA 60 006 10S/20S:

PVC +  **INOX**

| HS CODE |
|---|
| 76169990 |
| CARTON SIZE / PCS. |
| FA 60 006 10/S : 40 x 40 x 24 cm / 25 |
| FA 60 006 20/S : 40 x 40 x 24 cm / 20 |
| FA 60 006 XX: AET (UE) N°2777/11681-01/E00-00 |
| FA 60 006 XXS: AET (UE) N°2777/10792-02/E01-01 |
| Satra Technology Europe Ltd., N° 2777, Bracetown Business Park, Clonee, Dublin, D15YN2P, Ireland |
| MODULE D FI14/14003.02 |
| SGS Fimko Oy, N°0598 Takomotie 8, 00380 HELSINKI, Finland |

| | | | | |
|---|---|---------|--|---------|
| REF. | FA 60 006 10 FA 60 006 20 FA 60 006 10S FA 60 006 20S | | | |
| CE | EN 795:2012 Type B | | | |
|  | x1 | | | |
| LG. | 1.0 m | 2.0 m | 1.0 m | 2.0 m |
| MAT. | PVC /  STEEL Ø 8.0 mm | | PVC /  INOX Ø 8.0 mm | |
| R (kN) / MBS (kN) | 12 kN / 25 kN | | | |
|  | 0.56 kg | 0.80 kg | 0.46 kg | 0.74 kg |



Nombre d'utilisateurs
 Number of users
Cantidad de usuarios
 Quantità di utilizzatori
Anzahl der Benutzer

R (kN) / MBS (kN)

Résistance statique (en kN) / Résistance à la rupture
 Static strength / Minimum Breaking Strength
Resistencia estática (en kN) / Resistencia a la ruptura (en kN)
 Resistenza statica (in kN) / Resistenza alla rottura (in kN)
Statische Festigkeit (in kN) / Bruchfestigkeit (in kN)