




ARDON®
WORKWEAR
& OUTDOOR

ARDON® VERNOR S1P

SAFETY SHOES



DRY AIR



NONMETALLIC



ANTIBACTERIAL



REFLECTIVE



WASH-FRIENDLY



ESD



ARDON®
WORKWEAR
& OUTDOOR

ARDON® VERNOR S1P

SAFETY SHOES

ARTICLE

G3215

MATERIAL

Upper
Lining
Sole

MICROFIBER synthetic fiber with a thickness of 1,8 mm/ fabric
MESH laminated breathable fabric

PU/PU Superline, two-component spray coating, oil resistant,
anti-static, antislip,
Glassfiber 522
kevlar

Toe cap
Plate
Insole

ANATOMIC FOAM anatomically shaped EVA foam, supports
longitudinal and transverse arches, absorbs shocks in the heel area

SIZE

UNIT

PACKAGE

Units in a carton

Units in a box

36-48

pair

10 pairs

1 pair

DIMENSIONS

Carton H x W x D
(cm)

Carton (cbm)

36-48

36 x 39,5 x 67,5

0,096

Size EUR	35	36	37	38	39	40	41	42	43	44	45	46	47	48	49	50	51
Insole length mm	-	240	247	253	260	265	273	279	286	293	303	307	318	323	-	-	-
Foot length cm	-	23,5	24,2	24,8	25,5	26,0	26,8	27,4	28,1	28,8	29,8	30,2	31,3	31,8	-	-	-

DESCRIPTION

Safety shoe made of microfiber and fabric, machine washable up to 30 ° C. For greater comfort, it is equipped with an anatomically shaped, antistatic, antibacterial, ESD insole. Safety is ensured by a fiberglass toe and a flexible Kevlar insole. The lightweight dual-density polyurethane sole meets SRC anti-slip requirements. The model is ESD, ie it protects against electrostatic discharge and can therefore be used in EPA areas.

NORMS















(EU) 2016/425

EN ISO 20345:2011

Personal protective equipment – Safety footwear

Category

S1P SRC ESD

Categories	EN ISO 20345	
E - energy absorption in the heel area	✓	
FO - resistance to oils and fuels	✓	
A - antistatic footwear	✓	
SRC - resistance to slipping on ceramic floor tiles with SLS and on steel floors with glycerin	✓	
WR - upper resistant to water		
Safety toe cap for toe protection	✓	
P - resistance to punctures (protective insole)	✓	
SRA - slip resistance ceramic floor tiles with SLS		
HRO - resistance to contact heatup to 300 °C		
HI-insulation of the bottom of the shoe against heat		
CI-insulation of the bottom of the shoe against the cold		
Splatters of molten metal		
ESD – shoe protects against electrostatic discharge and can be used on EPA premises	✓	
The shoes do not contain metal parts	✓	
-		
-		
-		



ARDON®
WORKWEAR
& **OUTDOOR**

CODE	EAN	CARTON WEIGHT (KG)	UNIT WEIGHT (KG)
G3215/36	8592390080387	13.610	1.361
G3215/37	8592390080394	13.860	1.386
G3215/38	8592390080400	14.110	1.411
G3215/39	8592390080417	14.360	1.436
G3215/40	8592390080424	14.610	1.461
G3215/41	8592390080431	14.860	1.486
G3215/42	8592390080448	15.110	1.511
G3215/43	8592390080455	15.360	1.536
G3215/44	8592390080462	15.610	1.561
G3215/45	8592390080479	15.860	1.586
G3215/46	8592390080486	16.110	1.611
G3215/47	8592390080493	16.360	1.636
G3215/48	8592390080509	16.610	1.661



ARDON®
WORKWEAR
& **OUTDOOR**





ARDON®
WORKWEAR
& OUTDOOR

