



ARDON®
WORKWEAR
& OUTDOOR

ARDON® HOBARTLOW S3

SAFETY SHOES



DRY AIR



NONMETALLIC



WATER
REPELLENT



ANTIBACTERIAL



REFLECTIVE

TECHNICAL SHEET



ARDON®
WORKWEAR
& OUTDOOR

ARDON® HOBARTLOW S3

SAFETY SHOES

ARTICLE

G3217

MATERIAL

Upper First layer cowhide leather 1.8-2 mm, hydrophobic
Lining MESH-type laminated breathable fabric
Sole PU/rubber Superline, direct injection
Toe cap Fibreglass 522
Plate Kevlar
Insole ANATOMIC FOAM – anatomically shaped from EVA foam, antistatic, antibacterial, ESD

SIZE

36-48

UNIT

pair

PACKAGE

Units in a carton 10 pairs
Units in a box 1 pair

DIMENSIONS

36-48
Carton H x W x D (cm) 36 x 39,5 x 67,5
Carton (cbm) 0,096

Size EUR	35	36	37	38	39	40	41	42	43	44	45	46	47	48	49	50	51
Insole length mm		240	247	253	260	265	273	279	286	293	303	307	318	323			
Foot length cm		23,5	24,2	24,8	25,5	26,0	26,8	27,4	28,1	28,8	29,8	30,2	31,3	31,8			

DESCRIPTION

Safety shoes with an upper made of high-quality cowhide leather, leather tongue and ankle area, hydrophobic, reinforcement in the heel area, with fiberglass toe cap and Kevlar insole. PU/rubber sole resistant to contact heat up to 300°C.

TECHNICAL SHEET

NORMS









(EU) 2016/425

EN ISO 20345:2022

Personal protective equipment - Safety footwear

Category:

S3L SR FO HRO HI CI

Categories	EN ISO 20345	
E - energy absorption in the heel area	✓	
FO - resistance to oils and fuels	✓	
A - antistatic footwear	✓	
SR - resistance to slipping on ceramic floor with glycerin	✓	SR
WR - upper resistant to water	✓	
Safety toe cap for toe protection	✓	
PL - resistance to punctures (protective insole)	✓	
SRA - slip resistance ceramic floor tiles with SLS		SRA
HRO - resistance to contact heatup to 300 °C	✓	
insulation of the bottom of the shoe against heat	✓	HI
insulation of the bottom of the shoe against the cold	✓	CI
Splatters of molten metal		WG
ESD – shoe protects against electrostatic discharge and can be used on EPA premises		
The shoes do not contain metal parts	✓	0% METAL
-		
-		
-		



ARDON®
WORKWEAR
& **OUTDOOR**

CODE	EAN	CARTON WEIGHT (KG)	UNIT WEIGHT (KG)
G3217/36	8592390080707	14.20	1.420
G3217/37	8592390080714	14.55	1.455
G3217/38	8592390080721	14.70	1.470
G3217/39	8592390080738	14.95	1.495
G3217/40	8592390080745	15.20	1.520
G3217/41	8592390080752	15.55	1.555
G3217/42	8592390080769	15.80	1.580
G3217/43	8592390080776	16.01	1.601
G3217/44	8592390080783	16.30	1.630
G3217/45	8592390080790	16.55	1.655
G3217/46	8592390080806	16.80	1.680
G3217/47	8592390080813	17.05	1.705
G3217/48	8592390080820	17.30	1.730



ARDON®
WORKWEAR
& OUTDOOR





ARDON®
WORKWEAR
& OUTDOOR

