



ARDON®
WORKWEAR
& **OUTDOOR**

ARDON® VISPER GREY S1P


SAFETY SHOES



DRY AIR



**DEFUSE
CONTROL**



NONMETALLIC



REFLECTIVE

TECHNICAL SHEET



ARDON®
WORKWEAR
& OUTDOOR

ARDON® VISPER GREY S1P

SAFETY SHOES

ARTICLE

G3246

MATERIAL

Upper
 Lining
 Sole
 Toe cap
 Plate
 Insole

MESH/PU type fabric
 MESH laminated breathable fabric
 phylon/rubber, glued technology
 composite 459
 kevlar
 ANATOMIC FOAM anatomically shaped EVA foam, supports longitudinal and transverse arches, absorbs shocks in the heel area

SIZE

UNIT

PACKAGE

Units in a carton
 Units in a box

36-46
 pair

10 pairs
 1 pair

DIMENSIONS

Carton H x W x D
 (cm)
 Carton (cbm)

	36-42	43-46
Carton H x W x D (cm)	32.5 x 39.5 x 58	36.5 x 41.5 x 63
Carton (cbm)	0,0745	0,095

Size EUR	35	36	37	38	39	40	41	42	43	44	45	46	47	48	49	50	51
Insole length mm	-	239	245	251	257	263	269	275	281	287	293	299	-	-	-	-	-
Foot length cm	-	23,4	24,0	24,6	25,2	25,8	26,4	27,0	27,6	28,2	28,8	29,4	-	-	-	-	-

DESCRIPTION

Safety shoes with a sporty design with a breathable fabric upper, polyurethane is used to strengthen the upper and the toe cover. The footwear is equipped with an anatomically shaped insole, made of a material that effectively dampens the tread and ensures comfort even when worn for a long time. The shoes have a composite toe and a flexible Kevlar insole against punctures. The sole made of a combination of phylon / rubber material ensures a soft tread and at the same time provides the highest level of anti-slip properties.

NORMS

(EU) 2016/425

EN ISO 20345:2022

Personal protective equipment – Safety footwear

Category

S1PS FO SR

Categories

EN ISO 20345

E - energy absorption in the heel area

✓



FO - resistance to oils and fuels

✓



A - antistatic footwear

✓



SRC - resistance to slipping on ceramic floor tiles with SLS
and on steel floors with glycerin

✓



WR - upper resistant to water



Safety toe cap for toe protection

✓



P - resistance to punctures (protective insole)

✓



SRA - slip resistance ceramic floor tiles with SLS



HRO - resistance to contact heatup to 300 °C



HI-insulation of the bottom of the shoe against heat



CI-insulation of the bottom of the shoe against the cold



Splatters of molten metal



ESD – shoe protects against electrostatic discharge and can
be used on EPA premises



The shoes do not contain metal parts

✓



-

-

-



ARDON®
WORKWEAR
& OUTDOOR

CODE	EAN	CARTON WEIGHT (KG)	UNIT WEIGHT (KG)
G3246/36	8592390095725	10.00	1.000
G3246/37	8592390095732	11.50	1.150
G3246/38	8592390095749	12.00	1.200
G3246/39	8592390095756	12.50	1.250
G3246/40	8592390095763	13.00	1.300
G3246/41	8592390095770	13.50	1.350
G3246/42	8592390095787	14.00	1.400
G3246/43	8592390095794	15.50	1.550
G3246/44	8592390095800	16.00	1.600
G3246/45	8592390095817	16.50	1.650
G3246/46	8592390095824	17.00	1.700



ARDON®
WORKWEAR
& **OUTDOOR**





ARDON®

**WORKWEAR
& OUTDOOR**

