








gravity-s



HS CODE
56090090
CARTON SIZE / PCS.
80 x 40 x 24 cm / 10
AET N° 2777/10964-01/E06-01
Satra Technology Europe Ltd., N° 2777, Bracetown Business Park, Clonee, Dublin, D15YN2P, Ireland
MODULE D FI14/14003.02
SGS Fimko Oy, N°0598 Takomotie 8, 00380 HELSINKI, Finland

REF.	FA 30 610 15
LG. 	1.5 m (connectors included)
	140 KG
CE	EN 355:2002
MAT.	 PA 11 mm Polyamide
	45 mm
	ALU
	YES
+	VG 11.063
	1.65 KG



Largeur de l'absorbeur d'énergie
Width of the energy absorber
Ancho del absorbedor de energía
Larghezza del assorbitore di energia
Breite des Falldämpfers

Longueur Poids maxi utilisateur
Length Max. user weight
Longitud Peso máximo del usuario
Lunghezza Peso Max. dell'utente
Länge Höchstgewicht des Benutzers



Matière connecteurs
Material of connector
Material de los conectores
Materiale connettori
Material Verbinder



Homologué pour le travail à proximité d'arêtes vives
Approved for work near sharp edges
Homologado para trabajo cerca de aristas vivas
Omologato per lavoro in prossimità di spigoli vivi
Zugelassen für Arbeiten in der Nähe scharfer Kanten