



ARDON®
WORKWEAR
& OUTDOOR

ARDON® MASTERWIN 02

WORKING SHOES



WINTER



REFLECTIVE



**DEFUSE
CONTROL**



**WATER
REPELLENT**

TECHNICAL SHEET



ARDON®
WORKWEAR
& **OUTDOOR**

ARDON® MASTERWIN O2

WORKING SHOES

ARTICLE

G3389

MATERIAL

Upper

Lining

Sole

Insole

cowhide leather CRAZY HORSE, shoe tongue made of CORDURA fabric
synthetic fur

PU/PU, two-component spray coating, oil resistant, anti-static, antislip

ANATOMIC FOAM - anatomically shaped from EVA foam, supports
longitudinal and transverse arches, absorbs shocks in the
heel area, antistatic, antibacterial, ESD

SIZE

UNIT

PACKAGE

Units in a carton

Units in a box

36-48

pair

10 pairs

1 pair

DIMENSIONS

36-42

43-48

Carton H x W x D
(cm)

34 x 48 x 65

37 x 50 x 69

Carton (cbm)

0,106

0,128

Size EUR

35	36	37	38	39	40	41	42	43	44	45	46	47	48	49	50	51
----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----

Insole length mm

-	239	245	252	259	266	272	278	286	291	298	306	312	319	-	-	-
---	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	---	---	---

Foot length cm

-	23,9	23,5	24,2	24,9	25,6	26,2	26,8	27,6	28,1	28,8	29,6	30,2	30,9	-	-	-
---	------	------	------	------	------	------	------	------	------	------	------	------	------	---	---	---

DESCRIPTION

Shoes of managerial design. Upper with hydrophobic treatment is made of quality cowhide leather CRAZY HORSE, the tongue is made of durable CORDURA fabric. The elegant flat sole made of two-density PU has anti-slip SRC properties. Insulated with artificial fur.

TECHNICAL SHEET

NORMS

(EU) 2016/425

EN ISO 20347:2012

Personal protective equipment – Occupational footwear

Category

O2 SRC

Categories

EN ISO 20347

E - energy absorption in the heel area

✓



FO - resistance to oils and fuels

✓



A - antistatic footwear

✓



SRC - resistance to slipping on ceramic floor tiles with SLS
and on steel floors with glycerin

✓



WR - upper resistant to water

✓



Safety toe cap for toe protection



P - resistance to punctures (protective insole)



SRA - slip resistance ceramic floor tiles with SLS



HRO - resistance to contact heatup to 300 °C



HI-insulation of the bottom of the shoe against heat



CI-insulation of the bottom of the shoe against the cold

✓



Splatters of molten metal



ESD – shoe protects against electrostatic discharge and can
be used on EPA premises



The shoes do not contain metal parts



-

-

-



ARDON®
WORKWEAR
& **OUTDOOR**

CODE	EAN	CARTON WEIGHT (KG)	UNIT WEIGHT (KG)
G3389/36	8592390154453	15,0	1,50
G3389/37	8592390154460	15,4	1,54
G3389/38	8592390154477	15,7	1,57
G3389/39	8592390154484	16,0	1,60
G3389/40	8592390154491	16,2	1,62
G3389/41	8592390154507	16,4	1,64
G3389/42	8592390154514	16,6	1,66
G3389/43	8592390154521	16,9	1,69
G3389/44	8592390154538	17,2	1,72
G3389/45	8592390154545	17,5	1,75
G3389/46	8592390154552	17,9	1,79
G3389/47	8592390154569	18,3	1,83
G3389/48	8592390154576	18,7	1,87



ARDON®
WORKWEAR
& **OUTDOOR**





ARDON®
WORKWEAR
& OUTDOOR

